

AN ITALIAN POP BEAD.



Opustone®
STONE | TILE CONCEPTS



CHICCO

THE CHICCO COLLECTION COMES

FROM AN ALL-ITALIAN STORY:

THE WROUGHT VENETIAN.


A MATERIAL BELONGING TO EVERYONE,
PRESENT IN SOCIETY IN A TRANSVERSAL WAY.

FROM OFF-SITE RESIDENTIAL HOMES TO
ENTRANCE HALLS OF BOURGEOIS BUILDINGS IN
MILAN, FROM ELEMENTARY SCHOOL FLOORS TO

THE SIDEWALKS OF BOLOGNA'S PORTICOES.


GREY, GREEN, MUSTARD, PINK AND CACAO.

FIVE COLORS, THREE DESIGNS ON MESH.




Floor Onda Verde-Cacao






Floor Mosaic Regolo V/C/G






Mosaic Chicco Regolo G/V/C






Floor Verde 24"x48"






Mosaic Quadra Dark






Floor Mosaic Quadra Light






Floor Mosaic Onda Rosa-Greige / Rosa 24"x48"






Greige 24"x48" / Mosaic Regolo R/G/S






Senape 24" x48"





Senape 12"x12" / Rosa 12"x12"






CHICCO

TECHNOLOGY **HD DIGITAL COLORED BODY PORCELAIN**


FINISH **NATURAL RECTIFIED**

THICKNESS **9 MM**


CHICCO COLORS




CACAO




VERDE



GREIGE



ROSA



SENAPE

CHICCO SIZES




24"X48"




24"X24"




12"X12"




CHICCO MOSAIC PATTERNS




MOSAIC REGOLO V/C/G
14"X14"




MOSAIC REGOLO R/G/S 14"X14"




MOSAIC REGOLO G/V/C
14"X14"




MOSAIC QUADRA LIGHT
13"X13"




MOSAIC QUADRA DARK
13"X13"




MOSAIC ONDA V/C
11"X14"



MOSAIC ONDA R/G
11"X14"



MOSAIC ONDA S/G
11"X14"



CHICCO TECHNICAL FEATURES

STANDARD	FEATURES	REQUIRED VALUE	CHICCO
ISO 10545/2	SIZE		
	length and width	$\pm 0,6 \% / \pm 2 \text{ mm}$	$\pm 0,6 \% / \pm 2 \text{ mm}$
	thickness	$\pm 5 \% \pm 0,5 \text{ mm}$	$\pm 5 \% \pm 0,5 \text{ mm}$
	straightness of sides	$\pm 0,5 \% \pm 1,5 \text{ mm}$	$\pm 0,5 \% \pm 1,5 \text{ mm}$
	wedging	$\pm 0,5 \% \pm 2 \text{ mm}$	$\pm 0,5 \% \pm 2 \text{ mm}$
	flatness	$\pm 0,5 \% \pm 2 \text{ mm}$	$\pm 0,5 \% \pm 2 \text{ mm}$
ISO 10545/3	water absorption	$\leq 0,5 \%$	0,3 %
ASTM C373	water absorption	$\leq 0,5 \%$	meets the standards
ISO 10545/9	thermal shock	no visible alteration	resistant
ASTM C484	thermal shock	unaffected	unaffected
ISO 10545/12	frost/freeze resistance	no visible alteration	resistant
ASTM C1026	frost/freeze resistance	unaffected	unaffected
ISO 10545/13	chemical resistance	no visible alteration	LA HA
ASTM C650	chemical resistance		A
ISO 10545/4	breaking strength	$\geq 35 \text{ N/ mm}^2$	48 N/ mm^2
ISO 10545/7	visible abrasion resistance	CLASS I-V	PEI V GREIGE - ROSA PEI IV SENAPE - VERDE PEI III CACAO
ASTM C1027	visible abrasion resistance		CLASS IV
ISO 10545/14	stain resistance	$\geq \text{CLASSE 3}$	5
ASTM C1378	stain resistance	$\geq \text{CLASSE 3}$	5
DIN EN 16165	anti-slip		R10
DCOF	dynamic coefficient of friction	$> 0,42$	0,56
ANSI A137.1	aesthetic classes	V0-V4	V1

